Canon PIXMA MP980 series



Easy Setup Instructions For Apple AirPort Wireless Networks

These instructions are for setting up your PIXMA machine on an Apple AirPort wireless network in a Mac OS X environment. For all other environments, including USB connections, wired networks, non-AirPort wireless networks, and all Windows installations, please use the Getting Started Guide. Also for setting up additional computers on your network to access the machine, refer to the Getting Started Guide.

Before starting, please locate and write down the your network name and password. Since Apple recommends using the WPA/WPA2 encryption method for AirPort networks, these instructions are for configuring the machine on WPA/WPA2 encrypted networks.

Network Name (also called SSID):


Network password (if applicable):

Hardware Setup

Unpack the machine and prepare the hardware for use by following chapters 1 to 5 of the Getting Started Guide.




Driver/Software Install



and the other to the machine Make sure the machine is turned on

Connect one end of the USB cable to the computer



Turn on the computer, then insert the Setup CD-ROM into the CD-ROM drive.



Double-click the **Setup** icon.

If the CD-ROM folder does not open automatically, double-click the **CANON_IJ** icon on the desktop.





Enter your administrator name and password. Click **ÓK**.

If you do not know your administrator name or password, click **HeIp**, then follow the on-screen instructions.



Click Easy Install.

or, on the inside lower part of the machine


The drivers, application software, and on-screen manuals are installed automatically.

If the registration screen appears, follow the on-screen instructions to register your product. You will need your product serial number which is located on the packaging,





Follow on-screen instructions.







Click Restart.

When the computer restarts, Canon IJ Network Tool starts

Click Restart to restart the computer. After restarting the computer, remove the **Setup CD-ROM** and keep it in a safe place.





Connecting to AirPort Networks With a Single AirPort Access Point

Use These Instructions if Your Network Has Only One AirPort Networking Device (Single Time Capsule, AirPort Extreme, AirPort Express, etc.)

For Users With Multiple Access Points (Wireless Routers) Proceed to Section 3-B








When the Access Points screen appears, select an access point to use, then click Connect.


To connect to the access point with **WEP** or **WPA** displayed in the **Encryption** column, enter the network key (WEP key or WPA key) in **Network Password**, then click **Connect**.



If the Setup Preparations dialog box appears, confirm that preparation is complete, then click **OK**



menu, select MP980 series in Printers, then click OK.



Connecting to AirPort Networks With Multiple Access Points

Use These Instructions if Your Network Has Multiple AirPort Networking Devices (Including Time Capsule, AirPort Extreme, AirPort Express, etc.)

For example: Airport Extreme AND Time Capsule




On the Canon IJ Network Tool screen, select LAN connection, then click OK.




If the Setup Preparations dialog box appears, confirm that preparation is complete, then click OK.



Select Setup in the drop-down menu, select MP980 series in Printers, then click OK.



Select Use WPA2 from the drop-down menu. If the network uses WPA/WPA2 security, selecting **Use WPA** will give the same results.



Click Manual Setup.



Confirm the **Encryption** column to check the encryption method being




Enter the Network Name. (Also called SSID or Service Set Identifier that you would like the machine to







Check the Authentication Type and click Next.



Enter your Passphrase (network password) and click Next. For the encryption method, the default setting (TKIP: Basic Encryption) should be used.




Check the settings and click Finish.



Click Connect.





a. Disconnect the USB cable.

b. Click Next.







On the Connection Performance Measurement dialog box, click Next.



Confirm the measurement results, then click Finish.

Ensure that is displayed in Connection performance between the printer and the access point.

The Printer Setup Utility and Canon IJ Network Scanner Selector will start up.



• To check whether the new location is better, click **Remeasurement**. Measurement of the communication status is performed again.

Add the Machine

To troubleshoot the setup, refer to the printed manual: Network Setup Troubleshooting.

When using Mac OS X v.10.5.x, the machine's Card Slots are not accessible when using the machine over a network. To access the Card Slots from a computer using Mac OS X v.10.5.x, a USB cable must be used.

Mac OS X v.10.5.x



Wait for a while, then select Canon MP980 series and click Add.

When selecting the printer to add, make sure the **kind** listed for the printer is **canonijnetwork**. It may take up to 15 seconds for the network printer to appear in this list.



Select Canon MP980 series Network in TWAIN Data Source Name and the MAC address of the machine in Network Device List, then click Apply to use the machine as a scanner.



Confirm that a check mark is displayed, then click Exit to close the dialog box.

This completes the installation. The device is now installed and ready to use over the AirPort network.





Mac OS X v.10.4.x





When the **Printer List** screen appears, click **Add**.





Confirm that your **MP980 series** is added to the list of printers.

2



Click More Printers in the Printer
Browser screen





Select Canon MP980 series Network in TWAIN Data Source Name and the MAC address of the machine in Network Device List, then click Apply to use the machine as a scanner.

3



Select **Canon IJ Network** in the drop-down menu, select your machine's name in the list of printers, then click **Add**.





Confirm that a check mark is displayed, then click **Exit** to close the dialog box.

This completes the installation.
The device is now installed and ready to use over the AirPort network.

Mac OS X v.10.3.9





When the **Printer List** screen appears, click **Add**.





Select Canon MP980 series Network in TWAIN Data Source Name and the MAC address of the machine in Network Device List, then click Apply to use the machine as a scanner.

2



Select **Canon IJ Network** in the drop-down menu, select your machine's name in the list of printers, then click **Add**.





Confirm that a check mark is displayed, then click **Exit** to close the dialog box.

This completes the installation. The device is now installed and ready to use over the AirPort network.

3



Confirm that your **MP980 series** is added to the list of printers.

Apple, AirPort Extreme, Macintosh and Time Capsule are trademarks of Apple, Inc., registered in the U.S. and other countries.

Getting Help from Canon

Visit www.canontechsupport.com Call 1-800-828-4040 Monday - Friday (excluding holidays),

during the warranty period

Getting Help from Canon

Visit www.canon.ca
Call 1-800-652-2666
Monday - Friday (excluding holidays),
during the warranty period