



1 Unpack the Printer


- Carefully remove all items from the box.




i455 Series
Desktop Photo Printer



Paper Rest




Documentation
and Software Kit



i455 Series Print Head

Power Cord




Ink Tanks

BCI-24 Black

BCI-24 Color


2 Prepare the Printer

- Remove all shipping tape from the front and back of the printer.




Shipping
Tape

- Plug the power cord into the back of the printer and connect the other end to a power outlet.




- Press the Power button. The printer will initialize.



Power
Button


Power
Lamp

- Open the output tray, then open the front cover. The print head holder automatically moves to the center.



Front Cover

Output Tray




Serial Number

- Write down the serial number located to the right of the print head holder. You will need this later to register the product.

3 Install the Print Head


- Remove the print head from its package.



Tear at notch to open

- Remove the orange protective cap.


NOTE: Do not touch the electrical contacts or the print head nozzles.




Electrical
Contacts

Print Head
Nozzles


- Raise the gray lock lever on the printer.



- Slide the print head into the holder until it is securely seated.
Do not press it down.




- Lower the lever until it clicks into place.



4 Install the Ink Tanks

- Remove the black ink tank (BCI-24 Black) from its package and pull off the orange protective cap.



NOTE: Avoid ink at the bottom of the tank.




Protective Cap

- Insert the black ink tank into the slot on the right, then push in until the ink tank clicks into place.


IMPORTANT: For correct printer operation, make sure ink tanks are secure in slots.



- Repeat the procedure for the color ink tank (BCI-24 Color), inserting it into the remaining slot.



- Close the front cover, attach the paper rest and pull out the output tray.





NOTE: The printer will perform a print head cleaning after the cover is closed.

5 Connect the Printer and Load Paper

- Turn the printer off.

IMPORTANT: Be sure the printer is off before continuing, or the computer will attempt to install the printer driver before the printer is ready.


- Connect one end of a USB cable to the computer, the other to the printer.



USB Cable

USB Port

- Pinch the paper guide and slide it to the left. Load a sheet of blank paper in the paper rest. Slide the guide toward the left edge of the paper.



Paper
Guide


Continue with Step 6
on side two.



6 Windows® Printer Driver Installation and Print Head Alignment


Windows

- 1 Be sure to **TURN THE PRINTER OFF**.



NOTE: For Windows® XP or Windows 2000, log on to Windows as an Administrator before continuing.

IMPORTANT: If you see the Found New Hardware Wizard, click **Cancel**.




- 2 Close any open software applications, then insert the “Setup Software & User's Guide” CD-ROM. The setup program should run automatically.

NOTE: If the setup program does not run, click **Start**, then **Run**, then type **D:\msetup.exe**, where **D** is your CD-ROM drive.

- 3 Read the License Agreement, then click **Yes** to continue.

- 4 When the main menu appears, click **Install**.




- 5 When the Printer Port window appears, **TURN THE PRINTER ON** so the printer port (connection) can be automatically detected.




IMPORTANT: If your computer cannot detect a printer port, click **Help** and refer to the online instructions.

- 6 Register your product to ensure product support. Follow the on-screen instructions.



- 7 When the Terminate Installation window appears, click **OK**.

- 8 When the software menu appears, click **Install**.



- 9 When the Terminate Installation window appears, click **OK**, then **Exit**.


- 10 Click **Yes** when you are prompted to restart your computer.

- 11 Start the print head alignment procedure.


- a. For Windows XP/2000, click **Start**, select **Control Panel**, **Printers and Other Hardware**, then **Printers and Faxes**.
- b. Right-click the **Canon i455** icon, then click **Printing Preferences**.

NOTE: For Windows 98/Me, click **Start**, **Settings**, then **Printers**. Right-click the **Canon i455** icon, then click **Properties**.

- c. Click the **Maintenance** tab, then click the **Print Head Alignment** icon.




- d. When asked to start the print head alignment, click **OK** and follow the on-screen instructions.



- e. Click **YES** when prompted if the pattern printed successfully.

- 12 Compare the different patterns for each color on the printout.

- 13 For each color on the test printout, enter the number in the Print Head Alignment window that corresponds with the smoothest looking test pattern.



- 14 Click **OK** when finished.

- 15 Click **OK** to exit the Maintenance tab. Print head alignment is now complete.


6 Mac® OS X Printer Driver Installation and Print Head Alignment

Macintosh


For Mac OS 8.6 to 9.x printer driver instructions, refer to the "Appendix" of the *Quick Start Guide*.

- 1 Turn on your Mac and your printer and insert the “Setup Software & User's Guide” CD-ROM.

- 2 Double-click the CD-ROM icon, then the **Mac OS X** folder, then the **Printer Driver** folder.



- 3 Double-click the **i455 210.pkg** icon.




- 4 When the “Authenticate” screen appears, enter your administrator name and password, then click **OK**.

- 5 When the “Welcome to the BJ printer driver Installer” screen appears, click **Continue**.

- 6 Read the Software License Agreement and click **Continue**, then click **Agree**.

- 7 Select a destination for the printer driver to be installed. Then click **Continue**.



- 8 Click **Install**. When a message asking for your confirmation to proceed with the installation appears, click **Continue Installation**.


- 9 When the message “The software was successfully installed” appears, click **Restart**.

- 10 When the message asking you to align the print head appears, click **OK**.




- 11 Start the print head alignment procedure.


- a. Double-click the **Macintosh HD** icon, then the **Applications** folder. Double-click the **Utilities** folder, then the **Print Center** icon.
- b. When the Printer List screen appears, select **i455**, then click the **Configure** icon.



- c. Select **i455** and click **Select**.




- d. Click the down-arrow to select **Test Print**. Click the **Print Head Alignment** icon and follow the on-screen instructions.



- 12 Click **Quit** to exit the BJ Printer Utility. Print head alignment is now complete.

- 13 Access your CD-ROM again. From the **Application** folder, double-click on the software to be installed. Follow the on-screen instructions.



- 14 When the “Installation has finished” screen appears, click **OK**.

- 15 Register your product to ensure product support. Double-click on the **Product Registration** icon, found in the **Mac OS X** folder. Follow the on-screen instructions.