How to confirm a Password (Network Password) using "Keychain Access" (Mac)

When the following dialog is displayed during software installation, you can confirm a password (Network Password) using a Macintosh standard function of "Keychain Access." See below for details.

Preconditions)

- The Password / Network Password is registered by default, during initial setup of your wireless router, for Mac OS X v10.5. For Mac OS X 10.4, you will have to place a check in the check box for the password to be save in Keychain Access.
- Must be in a Macintosh computer with built-in wireless LAN port.
- Does not support Mac OSX 10.3.

evel	Encryption	Access Point Name (SSID)	Channel
Tal	WPA	001D73411004-2	8
Tal	WPA2	001D73411004-2	8
Tal	WPA	001D73411004-1	8
V .1	14/0.4	Atorm MILE 400 AD TAADOOGO	
		Network Information	on Update
o cor Conne		access point, enter the network passw	
Conne		access point, enter the network passw	

<Complement> The Access Point Name (SSID) is synonymous with a network name.

1. Confirm a Password (Network Password).

[Mac OSX 10.5]

(1) From Finder, go to Application, Utilities, and Keychain Access to launch Keychain Access.

(2) In the Keychain Access window, select "login" and "All Items" in "Category," then double click on the network name you are interested in.

Click to lock the	login keychain.			Q	
Keychains login System System Roots	AirMac Netw Kind: AirPort n Account: AirM Where: AirPort Modified: Tod	etwork password ac Network Network			
	Name	Kind	Date Modified	Expires	Keychain
	🔶 AirMac Network	AirPort network password	Today, 9:54		login
	AirPort Extreme	AirPort base station password	Today, 9:54		login
All Items]				
A. Passwords					
AppleShare					
Application					
Internet					
Certificates					
My Certificates					
% Keys					
Secure Notes					
	()
	(+) (i)	2 items			

NOTE: When there are the same network names, select the one with "AirPort network password" in "Kind."

[Mac OSX 10.4]

- (1) From Finder, go to Application, Utilities, and Keychain Access.app to launch Keychain Access.
- (2) In the Keychain Access window, select "login" and "All Items" in "Category," then double click on the network name you are interested in.

$\Theta \Theta \Theta$	Keychain Access		
Click to lock the login keychain.		٩	
Category All Items 	AirMac Network Kind: AirPort network password Account: AirMac Network Where: AirPort Network Modified: Today, 10:38		
P Keys	A Kind	Date Modified	Keychain
Secure Notes 🛛 🔥 AirN	AirPort network AirPort network password	Today, 10:38	login
^			

NOTE: When there are the same network names, select the one with "AirPort network password" in "Kind."

The following steps are common between Mac OSX 10.4 and Mac OSX 10.5

(3) In the AirMac Network window, select Show password.

	Attributes Access Control
Name:	AirMac Network
Kind:	AirPort network password
Account:	AirMac Network
Where:	AirPort Network
Comments:	
Show password	
	(Save Changes)

(4) The following warning message is displayed. Please enter the password for Keychain Access, then click Allow, or Always Allow.

\bigcap	Keychain Access wants to use your confidential information stored in "AirMac
1	Network" in your keychain.
1. K USA	To allow this, enter the "login" keychain password.
	Password:
▶ Details	
\bigcirc	Always Allow Deny Allow

NOTE: When a password is set to the Keychain Access function, you are required to enter the password for Keychain Access.

The default password for Keychain is the same as the login password for the Mac.

(5) A Password (Network Password) shows up in Show password.

		Attributes	Access	Control	<u>.</u>	
2	Name:	AirMac Netw	ork			_
	Kind:	AirPort netw	ork passwo	rd		
2	Account:	AirMac Netw	ork			
	Where:	AirPort Netw	ork			
	Comments:					
🗹 Sh	ow password:	abcdefgh				-
					Save Chang	ges
						_

2. How to enter the Password (Network Password) in the Access Points window

Please enter the Password (Network Password) confirmed in the step 1 "Confirm a Password (Network Password)." in the Access Points window as shown below.

- (1) Select the network name (Access Point Name (SSID)) specified in the step 1-(2).
- (2) When the Password (Network Password) is required, enter the password confirmed in the step 1-(4).
- (3) Click Connect.

etect	ed Access Po	Ints: Access Point Name (SSID)	Channel
T il	WPA	001D73411004-2	8
Tal.	WPA2	001D73411004-2	8
F al	WPA	001D73411004-1	8
			T
P .1	34/0.4	Network Information	ion Update
	nect to this		
o con Conne	nect to this	Network Informat	

<Complement>

- 1. If the same network names are displayed, select either one of them. (Either one will be fine.)
- 2. If the message "The Printer could not be connected to the specified access point" is displayed when clicking the Connect button, you may select the network name (Access Point name (SSID)) you are not using (e.g. the one your neighbor is using). In such a case, please select the other one.
- 3. To use the printer together with the multiple Access Points, click the Manual Setup button for the setup instead of the Connect button. For the setup method, see "Getting Started for Mac Users" included in the printer.

[How to register the Password (Network Password) in Keychain Access] [Mac OSX 10.5]

- (1) Select the network name from AirMac of the menu bar to connect the printer to the network.
- (2) In the dialog for entering the password, select Remember this network. Selected by default.

Password: ••••••
☐ Show password ✓ Remember this network
Cancel Ok

[Mac OSX 10.4]

- (1) Select the network name from AirMac of the menu bar to connect the printer to the network.
- (2) In the dialog for entering the password, select Remember password in my keychain. It is not selected by default, therefore, please select it.

00	AirPort	
The selected	d AirPort network requires a password t	to join.
Wirele	ss Security: WPA Personal	•
	Password:	
	Show password	
	Remember password in	my keychain
?	Cancel	ОК