








Menu Route Map



Settings marked with an asterisk (*) are only available when the optional paper drawer (drawer 2) is attached.



Menu Route Map

Scan Settings
USB Memory Settings
Change Default Settings
Scan Size
File Format
Encryption Level
Digital Signatures
Density
Original Orientation
Original Type
2-Sided Original
Sharpness
Data Size
Initialize Default Settings
E-Mail Settings
Change Default Settings
Scan Size
File Format
Encryption Level
Digital Signatures
Density
Original Orientation
Original Type
2-Sided Original
Sharpness
Data Size
Subject/Message
Reply To
Priority
Initialize Default Settings
I-Fax Settings
TX Function Settings
Change Default Settings
Scan Size
Density
Original Type
2-Sided Original
Sharpness
Subject/Message
Reply To
TX Terminal ID
Print Position
Initialize Default Settings
RX Print Settings
Print on Both Sides
RX Print Size
File Settings
Change Default Settings
Scan Size
File Format
Encryption Level
Digital Signatures
Density
Original Orientation
Original Type
2-Sided Original
Sharpness
Data Size
Initialize Default Settings
Register Unit Name (E-Mail/I-Fax)
Output File Image Settings
YCbCr TX Gamma Value
PDF (Compact) Image Quality Level
Image Level in Text/Photo Mode or Photo Mode
Data Size Priority, Image Quality Priority
Image Level in Text Mode
Data Size Priority, Image Quality Priority
OCR (Text Searchable) Settings
Smart Scan
256-bit AES Settings for Encrypted PDF*1
Acrobat 9.0 or Equivalent, Acrobat 10.0 or Equivalent

Settings marked with (*1) are enabled only when an optional Send PDF Security Feature Set is registered.
Settings marked with (*2) are available at a time, depending on the PDF encryption setting.

Memory Media Print Settings
Change Default Settings
Number of Copies
Paper
N on 1
2-Sided Printing
Set JPEG/TIFF Details
Print Date
Print File Name
Original Type
Brightness
Halftones
Set PDF Details
Brightness
Enlarge/Reduce to Fit Paper Size
Enlarge Print Area
Print Comments
Password to Open Document
Other
Halftones
Pure Black Text
Black Overprint
RGB Source Profile
CMYK Simulation Profile
Use Grayscale Profile
Output Profile
Matching Method
RGB Pure Black Process
CMYK Pure Black Process
Composite Overprint
Advanced Smoothing
Grayscale Conversion
Print Quality
Density
Fine Adjust
Toner Save
Special Smoothing Mode
Line Control
Default Display Settings
File Sort Default Settings
File Name Display Format
Initialize Default Settings

Settings marked with an asterisk (*) are only available when the optional paper drawer (drawer 2) is attached.

Printer Settings
Prioritize Driver Settings When Printing
Multi-Purpose Tray
Drawer 1
Drawer 2*1
Copies*2
2-Sided Printing*2
Default Paper*2
Default Paper Size
Default Paper Type
Paper Size Override
Print Quality*2
Density
Yellow
Magenta
Cyan
Black
Density (Fine Adjust)
Yellow
Magenta
Cyan
Black
Toner Save
Gratation
Special Smoothing Mode
Line Control
Layout*2
Binding Location
Gutter
Offset Short Edge (Front)
Offset Long Edge (Front)
Offset Short Edge (Back)
Offset Long Edge (Back)
Auto Error Skip*2
Timeout*2
Personality*2
Color Mode*2
Gratation Settings*2
Compressed Image Output*2
PCL*2
Paper Save
Orientation
Font Number
Point Size
Pitch
Form Lines
Character Code
Custom Paper
Unit of Measure
X dimension
Y dimension
Append CR to LF
Enlarge A4 Print Width

PS*2
Job Timeout
Print PS Errors
Pure Black Text
Black Overprint
RGB Source Profile
CMYK Simulation Profile
Use Grayscale Profile
Output Profile
Matching Method
RGB Pure Black Process
CMYK Pure Black Process
Halftones
Brightness
Composite Overprint
Advanced Smoothing
Grayscale Conversion

Settings marked with asterisk (*1) are only available when the optional paper drawer (drawer 2) is attached.
Settings marked with (*2) are only available for the MF729Cdw.

Menu Route Map

Adjustment/Maintenance	
Auto Adjust Gradation	
Full Adjust	
Quick Adjust	
Adjust Copy Image	
Auto Correction Settings	
Auto Adjust Image Regularly	Off, On
Correct Print Color Mismatch When Main Power is ON	Off, On
Correct Print Color Mismatch	
Display Timing for Cartridge Preparation Notification	
Auto	
Custom	1 to 20 to 99 (%)
Black Text Processing for Color	
Feeder	7 Levels
Platen Glass	7 Levels
Special Processing	
Special Paper Processing	
Manual Back Side Settings (for 2-Sided Only)	
Multi-Purpose Tray	Off, On
Drawer 1	Off, On
Drawer 2*	Off, On
Rough Paper Settings	
Multi-Purpose Tray	Off, On
Drawer 1	Off, On
Drawer 2*	Off, On
Envelope Cling Prevention	Off, On
Envelope Switch	Envelope 1, Envelope 2
Special Mode P	Off, On
Clean Fixing Assembly	
Clean ITB	
Clean Feeder	

Settings marked with an asterisk (*) are only available when the optional paper drawer (drawer 2) is attached.

System Management Settings	
Network Settings	-> Network Settings
Enable NFC	Off, On
System Manager Information Settings	
System Manager ID and PIN	
System Manager ID	
System Manager PIN	
System Manager Name	
Device Information Settings	
Device Name	
Location	
Department ID Management On/Off	Off, On
Security Settings	
Use SSL	Off, On
Use IPSec	Off, On
IPv4 Address Filter	
Outbound Filter	Off, On
Inbound Filter	Off, On
IPv6 Address Filter	
Outbound Filter	Off, On
Inbound Filter	Off, On
MAC Address Filter	
Outbound Filter	Off, On
Inbound Filter	Off, On
Select Country/Region	United States (US), Canada (CA), Brazil (BR), Mexico (MX), Other
Remote UI Settings	
Use Remote UI	Off, On
Remote UI Access Security Settings	Off, On
Remote UI Access PIN	
Auto Online for Remote Scan	Off, On
Restrict TX Function	
Address Book PIN	
Restrict New Destinations	Off, On
Restrict Resending from Log	Off, On
Coded Dial TX Confirmation	Off, On
Display Job Log	Off, On
Use as USB Device	Off, On
Store to USB Memory	Off, On (MF729Cdw) / Off, On (MF726Cdw)
Memory Media Print On/Off	Off, On (MF729Cdw) / Off, On (MF726Cdw)
Enable Product Extended Survey Program	Off, On
Display Consumables Information (RUI/Toner Status)	
Display Consumables Purchase Button (RUI)	Off, On
Toner Status Settings	Off, On (Displ. Consmbls. Purchase Btn.)
Enable Canon Mobile Scanning	Off, On
Google Cloud Print Settings	
Enable Google Cloud Print	Off, On
Google Cloud Print Registration Status	
Notify to Check Paper Settings	Off, On
Import/Export of Settings	
Import	
Export	
Secure Print Settings	
Off, On (Secure Print Deletion Time)	
10 to 30 to 240 (min.)	
Select OS for USB Connected PC	Mac OS, Windows, Other
PDL Selection (Plug and Play)	
Network	Fax, UFR II LT, UFR II LT (V4), PCL5*, PCL6*, PS*
USB	Fax, UFR II LT, UFR II LT (V4), PCL5*, PCL6*, PS*
Update Firmware	
Via PC	
Via Internet	
Version Information	
Register License*	
Initialize Key and Certificate	
Initialize Address Book	
Initialize Menu	
Preferences	
Timer Settings	
Common Settings	
Copy Settings	
Fax Settings	
Scan Settings	
Memory Media Print Settings	
Printer Settings	
System Management Settings	
Network Settings	
Enable NFC	
System Manager Information Settings	
Device Information Settings	
Department ID Management On/Off	
Security Settings	
Remote UI Settings	
Auto Online for Remote Scan	
Restrict TX Function	
Register LDAP Server	
Authentication Settings for Send Function	
Display Job Log	
Use as USB Device	
Store to USB Memory	
Memory Media Print On/Off	
Enable Product Extended Survey Program	
Information for Purchasing Consumables	
Enable Canon Mobile Scanning	
Google Cloud Print Settings	
Notify to Check Paper Settings	
Secure Print Settings	
Select OS for USB Connected PC	
PDL Selection (Plug and Play)	
Initialize All	
Initialize All	

Settings marked with an asterisk (*) are only available for the MF729Cdw.