

## 4K600STZ/4K601STZ menu setting list (English)

Tab	Contents of Menu	Menu Items			
Input settings	Aspect				
	Input level				
	Super white				
	Color space				
	Progressive				
	Input signal details				
Image adjustment	Image mode				
	Create profile (Displayed when [Image mode] is not [User 1] - [User 3])				
	Baseline image mode (Displayed when [Image mode] is [User 1] - [User 3])				
	Brightness				
	Contrast				
	Sharpness				
	Gamma				
	HDR range				
	Color adjustment	Color level			
		Color balance			
		Color temperature			
		R Gain			
		G Gain			
		B Gain			
		R Offset			
		G Offset			
		B Offset			
	Advanced adjustment	Ambient light (· This setting is available when the image mode is set to [Photo/sRGB]. · This setting is available when the baseline image mode is set to [Photo/sRGB].)			
		Random noise reduction			
		MPEG noise reduction			
		Dynamic gamma			
		Dynamic contrast			
		Colorimetry ([Colorimetry] can only be set when the image mode is [Video].)			
		HDR ([HDR] can only be set when the image mode is [Video].)			
		Mem. color correct	Flesh		
			Sky		
			Green		
		6-axis color adjust	Adjust	Hue (Green)	
				Saturation (Green)	
				Brightness (Green)	
				Hue (Cyan)	
				Saturation (Cyan)	
				Brightness (Cyan)	
				Hue (Blue)	
				Saturation (Blue)	
				Brightness (Blue)	
				Hue (Yellow)	
	Saturation (Yellow)				
	Brightness (Yellow)				
	Hue (Red)				
	Saturation (Red)				
Brightness (Red)					
Fine-Tune Gamma		White			
		Red			
		Green			
		Blue			
Light source mode					
Brightness level					

Install settings	Positional lock		
	Image flip H/V		
	Keystone		
	Professional settings	Panel drive mode	
		Multi input mode select	
		DVI optimizer	
		HDMI EDID mode select	
		RGB alignment	Micro-digital imageshift
			Registration
			Advanced registration
		High altitude	
		Operating mode	
		Marginal focus	
	Edge blending	Side	
	Color blending adjustment		
	Black level adjustment		
	Marker		
Lens - Position			
Screen color			
Iris			
Test pattern			
System settings	User screen settings	Logo capture	
		Logo position	
		No signal screen	
		Screen when blank	
		Projector on	
	On screen	Menu position	
		Menu display time	
		Menu rotation	
		Guide	
		Show input status	
		Lamp warning display	
		Air filter warning display	
		Overheat warning display	
	Remote control/Side control	Beep	
		Key repeat	
		Key lock	
		Remote control channel	
	Audio in terminal select		
	Serial communication	Baud rate	
		Data bits	
		Parity	
		Stop bit	
	Power supply settings	Standby power setting	
Quick startup			
Power management mode			
Power management duration			
Direct power on			
Motion blur reduction			
Language			
Other settings			

Network settings	Network settings lock		
	Network password setting		
	Register network password		
	Network (wired/wireless)		
	Detailed settings (wired)	MAC address	
		Detailed IPv4 address setting	IP address
			Subnet mask
			Gateway address
			DHCP
			TCP/IP settings
		IPv6	
		Detailed IPv6 address setting	Link local
			Auto
			Manual
			Gateway
			Auto settings
		Manual settings	
		Detailed settings (wireless)	Mode
	SSID		
	Security		
	Channel		
	Signal strength		
	MAC address		
	Wi-Fi Protected Setup		PBC
			PIN
	Manual settings		Mode
			SSID
			Security
			Channel
			Key ID
			Key type
	Key		
	Detailed IPv4 address		IP address
Subnet mask			
Gateway address			
DHCP			
TCP/IP settings			
IPv6			
Detailed IPv6 address setting	Link local		
	Auto		
	Manual		
	Gateway		
	Auto settings		
Manual settings			
PJLink			
AMX Device Discovery			
Crestron Room View			